



0338

No060-DoP-2019-01-21

British Standard	Title: Geotextiles and geotextile-related products	Intended Uses
EN 13251:2016	Characteristics required for use in earthworks, foundations and retaining structures	F, F + S
EN 13252:2016	Characteristics required for use in drainage systems	F, F + S, D
EN 13257:2016	Characteristics required for use in solid waste disposal	F, F + S, P
EN 13265:2016	Characteristics required for use in liquid waste containment projects	F, P

Essential Characteristics	Test Standard	Units	Performance	Confidence Limit
Tensile strength	BS EN ISO 10319	kN/m	MD 100 / CMD 100	-10
Elongation at maximum load	BS EN ISO 10319	%	MD 80 / CMD 80	±30
Dynamic perforation resistance	BS EN ISO 13433	mm	0	+1
Resistance to static puncture	BS EN ISO 12236	kN	19	-0.9
Opening size	BS EN ISO 12956	µm	<69	N.A.
Water permeability v_{H50}	BS EN ISO 11058	m/s	$10 \cdot 10^{-3}$	$-2 \cdot 10^{-3}$
Protection efficiency	BS EN ISO 13719	kN/m ²	$60 \cdot 10^3$	$-5 \cdot 10^3$
Pyramid puncture	BS EN ISO 14574	N	3458	-1037
Water flow capacity in the plane	BS EN ISO 12958	m ² /s	$2.9 \cdot 10^{-3}$	$-0.9 \cdot 10^{-3}$
Dangerous substances	National Regulations in force in EU Member States	-	Less than required by national regulations in EU Member States	-

Notes

Water flow capacity in the plane is obtained under a normal pressure of 20 KPa and hydraulic gradient of 1. It refers to a single band drain and it is normalised for an effective meter width of product.

Durability


To be covered within 1 month after installation (EN 12224).

Predicted to be durable for service lives up to 100 years in natural soils with $4 \leq \text{pH} \leq 9$ and soil temperatures $\leq 25^\circ \text{C}$ on the basis of the results of the test method EN ISO 13438 procedure A and test duration of 112 days.

System 2+: Notified factory production control certification body No. 0338 BTTG performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC.

The performance of the product GPT19 is in conformity with the declared performance in the table above. This declaration of performance is issued under the sole responsibility of the manufacturer GEOfabrics Limited.

Signed for and on behalf of GEOfabrics Limited by:



Alessandro Sartori - Technical Manager

Place and date of issue:

Leeds, West Yorkshire 21/01/2019