Declaration of Performance – GPT 19



0338 No060-DoP-2017-12-20

Standard Number	Title	Intended Uses
EN 13251:2016	Geotextiles for earthworks, foundations and retaining structures	F, F + S
EN 13252:2016	Geotextiles for drainage systems	F, F + S, D
EN 13257:2016	Geotextiles for solid waste disposal	F, F + S, P
EN 13265:2016	Geotextiles for liquid waste disposal	F, P

Essential Characteristics	Method	Units	Performance	Confidence Limit
Tensile strength	BS EN ISO 10319	kN/m	MD 100 / CMD 100	-10
Elongation	BS EN ISO 10319	%	MD 80 / CMD 80	±30
Dynamic perforation	BS EN ISO 13433	mm	0	+1
Resistance to static puncture	BS EN ISO 12236	kN	19	-0.9
Opening size	BS EN ISO 12956	μm	<69	N.A.
Water permeability	BS EN ISO 11058	m/s	10.10 ⁻³	-3.10 ⁻³
Protection efficiency	BS EN ISO 13719	kN/m²	60.10 ³	-5.10³
Pyramid puncture	BS EN ISO 14574	N	3458	-346
In-plane water flow	BS EN ISO 12958	m²/s	8.10-5	-2.10 ⁻⁵
	National Regulations		Less than required by	
Dangerous substances	in force in EU	-	national regulations in EU	-
	Member States		Member States	

Durability

To be covered within 1 month after installation (EN 12224).

Predicted to be durable for service lives up to 100 years in natural soils with $4 \le pH \le 9$ and soil temperatures $\le 25^{\circ}$ C on the basis of the results of the test method EN ISO 13438 procedure A and test duration of 112 days.

System 2+: Notified factory production control certification body No. 0338 BTTG performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance, assessment and evaluation of FPC and issued the certificate of conformity of the FPC.

The performance of the product GPT19 is in conformity with the declared performance in the table above. This declaration of performance is issued under the sole responsibility of the manufacturer GEOfabrics Limited.

Signed on behalf of GEOfabrics Limited by:

Clare Harvey - Compliance Manager

Place and date of issue:

Leeds, West Yorkshire 20/12/2017